



MODEL CC5

Model CC5 Cube Core Return Air Grille

Size	Area Ak	Inlet Velocity PS	200	300	400	500	600	700	800	900	1000
			.004	.008	.014	.022	.032	.044	.057	.072	.089
6x6	.25	CFM	50	75	100	125	150	175	200	225	250
	.25	NC	<15	<15	<15	<15	<15	<15	<15	16	19
8x6	.33	CFM	67	100	133	167	200	233	267	300	333
	.33	NC	<15	<15	<15	<15	<15	<15	<15	17	20
8x8	.44	CFM	89	133	178	222	267	311	356	400	444
	.44	NC	<15	<15	<15	<15	<15	<15	15	18	21
10x6	.42	CFM	83	125	167	208	250	292	333	375	417
	.41	NC	<15	<15	<15	<15	<15	<15	15	18	21
10x8	.56	CFM	111	167	222	278	333	389	444	500	556
	.54	NC	<15	<15	<15	<15	<15	<15	16	19	22
10x10	.69	CFM	139	208	278	347	417	486	556	625	694
	.68	NC	<15	<15	<15	<15	<15	<15	17	20	23
12x6	.50	CFM	100	150	200	250	300	350	400	450	500
	.49	NC	<15	<15	<15	<15	<15	<15	16	19	22
12x8	.67	CFM	133	200	267	333	400	467	533	600	667
	.65	NC	<15	<15	<15	<15	<15	<15	16	19	22
12x10	.83	CFM	167	250	333	417	500	583	667	750	833
	.82	NC	<15	<15	<15	<15	<15	15	18	21	24
12x12	1.00	CFM	200	300	400	500	600	700	800	900	1000
	.98	NC	<15	<15	<15	<15	<15	16	19	22	25
14x6	.58	CFM	117	175	233	292	350	408	467	525	583
	.57	NC	<15	<15	<15	<15	<15	<15	17	19	22
14x8	.78	CFM	156	233	311	389	467	544	622	700	778
	.76	NC	<15	<15	<15	<15	<15	15	18	21	24
14x14	1.36	CFM	272	408	544	681	817	983	1089	1225	1361
	1.33	NC	<15	<15	<15	<15	<15	17	20	23	26
16x16	1.78	CFM	356	533	711	889	1067	1244	1422	1600	1778
	1.74	NC	<15	<15	<15	<15	16	19	21	24	27
18x18	2.25	CFM	450	675	900	1125	1350	1575	1800	2025	2250
	2.21	NC	<15	<15	<15	<15	17	20	22	25	28
20x12	1.67	CFM	333	500	667	833	1000	1167	1333	1500	1667
	1.62	NC	<15	<15	<15	<15	16	18	21	24	27
20x20	2.78	CFM	556	833	1111	1389	1667	1944	2222	2500	2778
	2.72	NC	<15	<15	<15	15	18	21	23	26	29
22x22	3.36	CFM	672	1008	1334	1681	2017	2353	2689	3025	3361
	3.29	NC	<15	<15	<15	16	19	21	24	27	30
24x12	2.00	CFM	400	600	800	1000	1200	1400	1600	1800	2000
	1.96	NC	<15	<15	<15	<15	16	19	22	25	28
24x14	2.33	CFM	467	700	933	1167	1400	1633	1867	2100	2333
	2.29	NC	<15	<15	<15	<15	17	20	23	26	28
24x24	4.00	CFM	800	1200	1600	2000	2400	2800	3200	3600	4000
	3.96	NC	<15	<15	<15	17	19	22	25	28	31
26x4	.72	CFM	144	217	289	361	433	506	578	650	722
	1.06	NC	<15	<15	<15	<15	<15	<15	18	20	23
48x24	8.00	CFM	1600	2400	3200	4000	4800	5600	6400	7200	8000
	7.84	NC	<15	<15	17	20	22	25	28	31	34
		Throw	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Notes

All Units have been tested in accordance with ANSI / ASHRAE 70-2006. Data in table is derived from such testing
 Ps - Static pressure required to obtain listed cfm, units of inches water gauge (in. wg)
 NC- Calculated noise criteria using 10 dB per octave room attenuation (dimensionless).

For sizes not shown, refer to online tools **GRD Selection Program** performance calculator on Home Page